



Fittings & Accessories

AKRON BRASS COMPANY | PH. 800.228.1161 (330.264.5678) | FAX 800.531.7335 (330.264.2944) | www.akronbrass.com



630
Angle Elbow
SWIVEL FEMALE x MALE
• 2 1/2" & 3" sizes in 30°
(64 & 76 mm)
• 4" size 45° (102 mm)
† 2 1/2" x 2 1/2"
(65 x 65 mm)
3" x 2 1/2"
(75 x 65 mm)
3" x 3"
(76 x 76 mm)
◊ 4" x 4"
(100 x 100 mm)

632
90° Suction Elbow
FEMALE x MALE
† ◊ 2 1/2" x 2 1/2"
(65 x 65 mm)
◊ 4" x 4"
(100 x 100 mm)
† 5" x 5"
(125 x 125 mm)

655
90° Front Suction Elbow with Strainer
FEMALE NPT x MALE NH
4" x 4"
(100 x 100 mm)
4" x 4 1/2"
(100 x 114 mm)
◊ 5" x 5"
(125 x 125 mm)
◊ 5" x 6"
(125 x 150 mm)

635
90° Continuous Swiveling Elbow
FEMALE NPT x MALE NH or NPSH
• Full 2" (51 mm) waterway with cast-in turning vane
1 1/2" 2" or 2" female x 1 1/2" male (38 or 50 x 38 mm)
2 7/16" or 4 5/8" length
2 1/2" female x 2 1/2" male (63 mm x 65mm)
5" length

347
Hose Plug
• Available with rocker lug
• Chain optional through 4" (102 mm)
† 1 1/2" (38 mm)
† 2" (50 mm)
† 2 1/2" (65 mm)
† 3" (75 mm)
3 1/2" (89 mm)
† 4" (100 mm)
4 1/2" (114 mm)
5" (125 mm)
6" (150 mm)

KEY
√ Optional with strainer
* Pyrolite
† Cast or chrome
◊ Chrome Ends with Red Paint
Cast brass

NOTE: All items are chrome, unless noted otherwise.



326
British Instantaneous Adapter
MALE x BIM
*# 1 1/2" x 2 1/2"
(38 x 38 mm)
*# 2 1/2" x 2 1/2"
(65 x 65 mm)

335
Double Female Swivel Adapter
* † 1 1/2" (38 mm)
† 2" (50 mm)
* † 2 1/2" (65 mm)
3" X 2 1/2" (75 x 38 mm)
† 3" (75 mm)

336
Double Male Adapter
* † 1 1/2" (38 mm)
† 2" (50 mm)
* † 2 1/2" (65 mm)
3" X 2 1/2" (75 x 65 mm)
† 3" (75 mm)
4" (100 mm) Pyrolite only

354
Female Swivel to Male Adapter
• Long handle or rocker lug
2 1/2" x 2 1/2" (65 x 65 mm)
2 1/2" x 3" (65 x 75 mm)
2 1/2" x 3 1/2" (65 x 89 mm)
2 1/2" x 4" (65 x 100 mm)
2 1/2" x 4 1/2" (65 x 114 mm)
2 1/2" x 5" (65 x 125 mm)
2 1/2" x 6" (65 x 150 mm)
3" x 2 1/2" (75 x 65 mm)
3" x 3" (76 x 76 mm)
3" x 3 1/2" (75 x 89 mm)
3" x 4" (75 x 100 mm)
3" x 4 1/2" (75 x 114 mm)
3 1/2" x 2 1/2" (89 x 89 mm)
3 1/2" x 3" (89 x 75 mm)
3 1/2" x 4 1/2" (89 x 114 mm)
4" x 2 1/2" (100 x 64 mm)
4" x 3" (100 x 75 mm)
4" x 4 1/2" (100 x 114 mm)
4" x 5" (100 x 125 mm)
4" x 6" (100 x 153 mm)
4 1/2" x 2 1/2" (114 x 65 mm)
4 1/2" x 4" (114 x 100 mm)
4 1/2" x 4 1/2" (114 x 114 mm)
4 1/2" x 5" (114 x 125 mm)
4 1/2" x 6" (114 x 150 mm)
5" x 4" (125 x 100 mm)
5" x 4 1/2" (125 x 114 mm)
5" x 6" (125 x 150 mm)
6" x 2 1/2" (150 x 65 mm)
6" x 4" (150 x 100 mm)
6" x 4 1/2" (150 x 114 mm)
6" x 5" (150 x 127 mm)

357
Double Female Swivel Adapter
• Long handle or rocker lug
3 1/2" x 3 1/2" (89 x 89 mm)
4" x 2 1/2" (100 x 65 mm)
4" x 3 1/2" (100 x 89 mm)
* 4" x 4" (100 x 100 mm)
* 4 1/2" x 2 1/2" (114 x 114 mm)
4 1/2" x 3" (114 x 75 mm)
4 1/2" x 4" (114 x 100 mm)
* 4 1/2" x 4 1/2" (114 x 114 mm)
* 5" x 2 1/2" (125 x 65 mm)
* 5" x 4" (125 x 100 mm)
* 5" x 4 1/2" (125 x 114 mm)
5" x 5" (125 x 125 mm)
* 6" x 2 1/2" (150 x 65 mm)
6" x 3 1/2" (150 x 89 mm)
6" x 4" (150 x 100 mm)
* 6" x 4 1/2" (150 x 114 mm)
* 6" x 5" (150 x 125 mm)
* 6" x 6" (150 x 150 mm)

- 1422 Rigid Direct Connect Base**
- For adapting an 1 1/2" nozzle base to a 2 1/2" hose line
 - Pyrolite® construction
 - 2 1/2" female x 1 1/2" male
 - Tapered waterway for reduced turbulence
 - Weight: 12 oz. (340 g)



Style 1422

- 422 Rigid Direct Connect Base**
- Same as Style 1422 except brass with cast or chrome finish
 - Weight: 1 1/2 lbs. (.7 kg)



345
Hose Cap
• Available with rocker lug
• 2" and 3" (51 & 76 mm) available with long handle
• Chain optional
† 3/4" GHT (19 mm)
† 1" (25 mm)
† 1 1/2" (38 mm)
† 2" (50 mm)
† 2 1/2" (65 mm)
† 3" (75 mm)
† 3 1/2" (89 mm)



KEY	
✓	Optional with strainer
*	Pyrolite
†	Cast or chrome
◊	Chrome Ends with Red Paint
#	Cast brass

NOTE: All items are chrome, unless noted otherwise.



331 Long Internal Lug Adapter FEMALE NPT x MALE
† 2 1/2" only (65 mm)

330 Short Internal Lug Adapter FEMALE NPT x MALE
† 1 1/2" x 1 1/2" (38 x 38 mm)
✓† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)
† 3" x 3" (75 x 75 mm)

337 Rigid Female to Male Adapter
† 3/4" GHT x 1" (19 x 25 mm)
† 1" x 3/4" GHT (25 x 19 mm)
† 1" x 1" (25 x 25 mm)
† 1" x 1 1/2" (25 x 38 mm)
† 1 1/4" x 1" (32 x 25 mm)
† 1 1/2" x 3/4" (38 x 19 mm)
† 1 1/2" x 1" (38 x 25 mm)
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 1 1/2" x 2" (38 x 50 mm)
† 1 1/2" x 2 1/2" (38 x 65 mm)
† 2" x 1" (50 x 25 mm)
† 2" x 1 1/2" (50 x 38 mm)
† 2" x 2" (50 x 50 mm)
† 2" x 2 1/2" (50 x 65 mm)
† 2 1/2" x 3/4" GHT (65 x 19 mm)
† 2 1/2" x 1 1/2" (65 x 38 mm)
† 1 1/2" x 1" (38 x 25 mm)
*† 2 1/2" x 1 1/2" (65 x 38 mm)
† 2 1/2" x 2" (65 x 50 mm)
*† 2 1/2" x 2 1/2" (65 x 65 mm)
† 2 1/2" x 3" (65 x 76 mm)
† 2 1/2" x 3 1/2" (65 x 89 mm)
† 3" x 1 1/2" (75 x 38 mm)
† 3" x 2 1/2" (75 x 65 mm)
† 3" x 3" (75 x 75 mm)
† 3" x 3 1/2" (75 x 89 mm)
† 3 1/2" x 2 1/2" (89 x 65 mm)
† 3 1/2" x 3" (89 x 75 mm)

356 Rigid Female to Male Adapter
† 2 1/2" x 4" (65 x 100 mm)
† 3 1/2" x 4" (89 x 100 mm)
† 4" x 2 1/2" (100 x 65 mm)
† 4" x 3" (100 x 75 mm)
† 4" x 3 1/2" (100 x 89 mm)
† 4" x 3" (100 x 75 mm)
† 4" x 3 1/2" (100 x 89 mm)
✓† 4" x 4" (100 x 100 mm)
† 4" x 4 1/2" (100 x 114 mm)
† 4" x 5" (100 x 125 mm)
† 4" x 6" (100 x 153 mm)
† 4 1/2" x 2 1/2" (114 x 65 mm)
† 4 1/2" x 3" (114 x 75 mm)
† 4 1/2" x 4" (114 x 100 mm)
† 4 1/2" x 4 1/2" (114 x 114 mm)
† 4 1/2" x 5" (114 x 125 mm)
† 4 1/2" x 6" (114 x 150 mm)
† 5" x 2 1/2" (125 x 65 mm)
† 5" x 3" (125 x 75 mm)
† 5" x 4" (125 x 100 mm)
✓† 5" x 4 1/2" (125 x 114 mm)
† 5" x 5" (125 x 125 mm)
† 5" x 6" (125 x 150 mm)
† 6" x 3" (150 x 75 mm)
† 6" x 4" (150 x 100 mm)
✓† 6" x 4 1/2" (150 x 114 mm)
✓† 6" x 5" (150 x 125 mm)
† 6" x 6" (150 x 150 mm)



338 Suction Lug Adapter with Strainer FEMALE NPT x FEMALE SWIVEL
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)
3" x 3" (75 x 75 mm)
3" x 3 1/2" (75 x 89 mm)
3 1/2" x 3 1/2" (89 x 89 mm)
3 1/2" x 4" (89 x 100 mm)
4" x 3 1/2" (100 x 89 mm)
† 4" x 4" (100 x 100 mm)

361 Double Male Hex Nipple
3/4" x 3/4" (19 x 19 mm)
GHT or NPSH
1" x 3/4" GHT (25 x 19 mm)
† 1" x 1" (25 x 25 mm)
1 1/2" x 1" NH (38 x 25 mm)
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 2" x 1 1/2" NH (50 x 38 mm)
† 2" x 2" (50 x 50 mm)
† 2 1/2" NH or (65 mm)
NPT, or NPSH
† 2 1/2" x 2 1/2" (65 x 65 mm)

362 Female to Male Hex Nipple
† 3/4" NPT x 3/4" NH (19 x 19 mm)
or NPSH
† 3/4" GHT (19 mm)
† 1" x 3/4" GHT (25 x 19 mm)
† 1" x 1" (25 x 25 mm)
1 1/2" x 3/4" GHT (38 x 19 mm)
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 2" x 1 1/2" (50 x 38 mm)
† 2" x 2 1/2" (50 x 65 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)

- 631 60° Angle Elbow**
- For high-rise stand pipes
 - Pyrolite® finish
 - 2 1/2" female x 2 1/2" male
 - Weight: 1 7/8 lbs. (.9 kg)

- 633 30° Discharge Elbow**
- For use on the pumper discharge
 - Chrome finish
 - 2 1/2" NPT X 2 1/2" NH weight: 3 lbs. (1.4 kg)

- 650 Swiveling Elbow**
- For aerial applications
 - Pyrolite finish
 - Full flow waterway with cast-in turning vanes for reduced friction loss
 - Available in 4", 5" and 6" sizes
 - Height 12 1/2"
 - Weight: 8 3/4 lbs. (4 kg)



Style 631



Style 650



Style 633



Hose Equipment

AKRON BRASS COMPANY | PH. 800.228.1161 (330.264.5678) | FAX 800.531.7335 (330.264.2944) | www.akronbrass.com

Suction Strainers

339 Basket Suction Strainer

An economical, high capacity suction strainer with galvanized plated mesh for longer life.

- Available in 2 1/2" (65 mm) and 5" (127 mm) size NH and other selected threads
- 2 1/2" (65 mm) barrel strainer length: 4 7/8" (124 mm), weight: 2 lbs. (.9 kg)

340 Barrel Suction Strainer

Heavy-duty barrel suction strainer with rope eye. Capable of flowing large volumes of water to match today's high capacity pumps.

- Pyrolite® finish
- Available in 4" (102 mm) through 6" (152 mm) NH; 5" (127 mm) weight: 4 1/4 lbs. (1.9 kg)
- 5" (127 mm) barrel strainer length: 10" (254 mm), weight: 4 1/4 lbs. (1.9kg)

344 Barrel Suction Strainer

Heavy-duty barrel suction strainer designed to accommodate large volumes of water.

- Steel with nickel chrome plate
- Available in 2 1/2" (65 mm) NH and other selected threads
- 2 1/2" (65 mm) barrel strainer length: 6 7/8" (175 mm), weight: 3 lbs. (1.4 kg)



Style 339



Style 344

Hose Jackets

772 2 1/2" (64 mm) Hose Jacket

For emergency repair of burst or leaky hose - or as an emergency adapter for the connection of two hose lines with different threads in situations where pressures do not exceed 150 psi (10.34 bar).

- Akrolite® construction and molded neoprene liner
- Fits all 2 1/2" (64 mm) hose from 2 3/4" (70 mm) to 3 5/16" (84 mm) O.D.
- Length: 13" (330 mm), weight: 16 1/2 lbs. (7.5 kg)

773 3" (76 mm) Hose Jacket

- Same as Style 772, except: Fits 3" (76 mm) hose from 3 1/2" (89 mm) to 3 3/4" (95 mm) O.D.
- Length: 15" (381 mm), weight: 26 3/4 lbs. (12.1 kg)

352 2 1/2" (64 mm) Hose Jacket Mounting Peg

- For mounting 2 1/2" (64 mm) hose jacket on a running board or in a compartment
- Length: 13 3/8" (340 mm), weight: 2 1/4 lbs. (1 kg)

353 3" (76 mm) Hose Jacket Mounting Peg

- Same as Style 352, except for 3" (76 mm) hose jacket
- Length: 15 1/2" (394 mm), weight: 3 3/4 lbs. (1.7 kg)



Style 772

Hose Clamp

588 Hose Clamp

- For use on double-jacketed woven hose up to 3" (76 mm)
- Rubber jaws and lock
- Lightweight for easy handling
- Supplied with Style 589 mounting bracket
- Length: 30" (762 mm), weight: 16 lbs. (7.3 kg)

589 Hose Clamp Mounting Bracket

- For Style 588 Hose Clamp



Style 588



Equipment Holders

- 350 Mounting Plate**
- Chrome plated
 - Available in 1" (25 mm) to 6" (152 mm) sizes
 - For securing equipment with female threads
 - Screw type mount with bolt holes in the center for neat appearance
 - 2 1/2" (64 mm) weight: 12 oz. (340 g)
- 373 E-Z - Lok Nozzle Holder**
- Available in 1 1/2" (38 mm) and 2 1/2" (64 mm) sizes - Must specify
 - For securing equipment with female threads
 - Quick release for fast and easy mounting and removal
 - Weight: 1 5/8 lbs. (.7 kg)



Style 350



Style 373

Taps And Dies

- 90 1 1/2" (38 mm) and 2 1/2" (64 mm) Die**
- For chasing damaged brass male threads
 - Made of hardened tool steel
 - Available in NH, and NPSH only
 - 2 1/2" (64 mm) weight: 3 1/4 lbs. (1.5 kg)
- 91 1 1/2" (38 mm) and 2 1/2" (64 mm) Tap**
- Same as Style 90, except for chasing female threads
 - 2 1/2" (64 mm) weight: 3 1/2 lbs. (1.6 kg)



Style 90



Style 91

Sprinkler Shutoff

- 1078 Quickfit Sprinkler Shutoff**
- Simple, quick, positive shutoff for many types of sprinkler heads with openings of approximately 7/8" (22 mm) wide by 1" (25 mm) high or 3/4" (19 mm) wide by 1 1/16" (43 mm) high. Allows sprinkler heads out of fire area to be shut off. Weight: 6 oz. (170 g)



Style 1078

Lubricants

Repair instructions for Akron® products often call for lubricants to ensure proper repair and long term service.

- 9201 Parker® O-Lube**
- 4 oz. (113 g) tube
- 9202 Low-Temp Lubriplate®**
- 10 oz. (284 g) tube
- 9203 Low-Temp Lubriplate**
- 14 1/2 oz. (411 g) cartridge



Style 9201



Style 9202



Style 9203



Specialized Tools

AKRON BRASS COMPANY | PH. 800.228.1161 (330.264.5678) | FAX 800.531.7335 (330.264.2944) | www.akronbrass.com

Tool Kit

9200 Nozzle Repair Tool Kit

Self-contained kit includes the tools needed to repair standard Akron® Nozzles. All tools packaged in a carrying case.

- Tools include:
 - Hammer
 - Pliers
 - Open Face Spanner
 - Strap Wrench
 - O-Ring Lubricant
 - 2 O-Ring Tools
 - 2 Screw Drivers
 - 2 Punches
 - 3 Swivel Adapter Tools
 - 8 Hex Wrenches
- Size: 12" x 8 1/2" x 2 3/4" (305 mm x 2116 mm x 70 mm)
- Weight: 8 1/2 lbs. (3.9 kg)



Style 9200

Expansion Units

75 Expansion Units

- Available in 1 1/2", 1 3/4", 2", 2 1/2" - 6" (38 mm, 44 mm, 51 mm, 64 mm - 152 mm) sizes
- Expansion Units consist of hardened steel segments, segment holder and drawbar
- Hard chromed for longer life
- The 2 1/2" (64 mm) and 3" (76 mm) sizes use a 2 1/2" (64 mm) drawbar and 3 1/2" (89 mm) - 6" (152 mm) use a 3 1/2" (89 mm) drawbar



Style 75

Leaf Thread Gauge

70 Leaf Thread Gauge

- Used to determine number of threads per inch



Style 70

Specialty Tools

50 Utility Bar

- A zinc-plated, all-purpose, forcible entry tool.
- Weight: 8 1/2 lbs. (3.9 kg), length: 26" (660 mm)



Style 50



Heat Sensors

9011 Heat Sensor with Laser Sight

- Only 11 oz.
- Backlit $7/16$ " (11.1 mm) LCD display
- Detects surface temperature of -25° to 999°F (-32° to 535°C)
- Includes 9V battery and compact storage case
- D:S-12:1

Mini Heat Sensor with Laser Sight

- Only 8 oz. (227 g)
- Backlit LCD display
- Detects surface temperature of 0° to 525°F (-18° to 275°C)
- Includes 9V battery
- D:S-8:1



Style 9011

Style 9011
Mini

Hose Accessories

583 Hose Hoist

- Akrolite™ construction
- For raising or lowering hose, ladders, etc. to and from the roof or through windows
- Weight: $7\frac{1}{8}$ lbs. (3.4 kg)

78 Hose & Ladder Strap

- Secures hose up to 3" (76 mm) on ladders, fire escapes, etc. and aids in the handling of hose
- Anodized aluminum fittings with 1" (25 mm) wide, flat, water-resistant nylon webbing
- Fits ladder rungs up to 2" (51 mm) O.D.
- Weight: 1 lbs. (.5 kg)



Style 583



Style 78